PFAFF® Industrial

Excellence in seaming



335

Cylinder-bed sewing machine
for industry and handcraft

335

Universal cylinder-bed machine for use in:
Small leather goods, leather garments, upholstery, shoes, etc.

Areas of Application:

- Working on tubular or pre-attached articles
- Standard sewing work on leather wear, bags and leathercraft articles
- Binding of shoes and leather wear with leather-, imitation leather- or textile tape
- Piping work on bags, suitcases and upholstery

Features:






- Very good feeding properties due to the unison feed
- Excellent sewing quality with high perfomance and sewing reliability
- Precise and consistent stitch setting at large spectrum of materials/fabrics
- Very neat bindings, even inside and outside curves, thanks to the moving binder and tape is held close to the binding edge (subclass -17/01)
- Fewer bobbin changes due to the large hook (40% more bobbin capacity than standard hook)
- Rugged and durable machine construction - Easy to maintain machine concept
- The high top feed lift (7 mm) allows trouble-free sewing of thick materials and an easy sewing over cross seams
- Easy loading and unloading – even of bulky material – due to a high fabric clearance of 14 mm
- Distance of the front edge of the cylinder arm to the needle: 9 mm - Cylinder arm diameter: 51 mm
- Original PFAFF Industrial machines have an additional security label with several security features on the machine head. The advantage of this security label is the protection against growing product piracy.







Versions:

Type	Model								
		-900/56	-911/97		-2/27	-6/01	-17/01-650/03	-39/21*	-40/64*
335	B				x	x	x	x*	x*
335**	B	●	●	●	x	x	x	x*	x*

For portfolio work. A smaller version of the kit (part set is smooth). Ruler mounted on the forearm.

For general sewing. Standard form of the kit.

For binding operations, 90 ° tape feeder, attachment on swing- mounted carrier mounted (without binder).

For binding operations, both edges folded in, 90 ° tape feeder, attachment on swing-away carrier mounted.

Sewing in piping between two material plies, piping guide retractable, attachment fixed. Available as N 2.5 (stitch length max. 2.5 mm) or for max. stitch length of 4.5 mm.

<u>Remarks:</u>

x Selectable sub-class

* Sub-class has to be ordered separately (Sample and fabric are required)

** An air filter/regulator for pneumatic devices -925/04 is required





PFAFF® Industrial

Specifications:

Stitchtype:
301 (lockstitch)

Max. sewing speed:
2800/s.p.m.

Max. stitch length:
6 mm (N)

Model: B

Clearance under the sewing foot:
max. 14 mm

Top feed stroke:
7 mm

Clear work space:
265 mm

Clear work height:
115 mm

Cylinder bed dia:
51 mm

Cylinder bed circumf.:
approx. 165 mm

Needle system:
134-35

Needle thickness:
80-100

Thread type:
synth. 40/3

Balance wheel eff. dia:
80 mm

Working air pressure:
6 bar

Net weight (head):
approx. 32 kg

Net weight (head in carton):
approx. 40 kg

PFAFF is the exclusive trademark of VSM Group AB. | PFAFF Industriesysteme und Maschinen GmbH is an authorized licensee of the PFAFF trademark.

BLUEcoMPETENCE Alliance Member
Partner of the Engineering Industry Sustainability Initiative

Europäische Union
Wachstum durch Innovation – EFRE

Printed in Germany No. 296-12-18862 (e) 02/15

PFAFF Industriesysteme und Maschinen GmbH

Hans-Geiger-Str. 12 – IG Nord
D-67661 Kaiserslautern

Telefon: +49-6301/3205-0
Telefax: +49-6301/3205-3171
E-mail: info@pfaff-industrial.com